



TECHNO-COMMERCIAL PROPOSAL

SS316 Inline Spring-Loaded Check Valve — G1" BSP Female Both Ends

OIL & GAS / OFFSHORE -- API 6D / NACE

1. COVER LETTER

Thank you for your enquiry for oil and gas application valves. Supreme Valves India is pleased to submit this Techno-Commercial Proposal for API 6D / NACE MR0175 compliant valves suitable for sour service, offshore, and petrochemical applications.

2. CUSTOMER & PROJECT DETAILS

Quotation Reference	SV/QTN/2026/SND/001
Quotation Date	05 June 2026
Customer	Sandvik Mining and Rock Technology India Pvt Ltd
Contact Person	Sudhir Shendge
Email	sudhir.shendge@sandvik.com
Phone	--
Address	Udaipur, Rajasthan, India
Project / Location	Udaipur — Mining / Rock Technology
Application	Inline non-return protection for hydraulic / process feed line
RFQ Subject	Request for quotation of Check Valve
RFQ Date	04 June 2026

3. SCOPE OF SUPPLY

Sr	Description	Size	Qty	Unit Price (INR)	Total (INR)
1	<p>Inline Spring-Loaded Check Valve SS316 (AISI 316) body inline spring-loaded check valve. G1" BSP female inlet and G1" BSP female outlet. Maximum working pressure 200 bar. Maximum differential pressure 5 bar. Opening / cracking pressure 0.15 to 0.25 bar. Nominal flow capacity 160 l/min. Viton (FKM) seals — EPDM available on request. Spring-loaded non-return design; mountable in any orientation. Hydrostatic test certificate included.</p> <p>Specs: Equivalent to Kytola 2680-B G1" configuration per customer datasheet; other makes acceptable as stated in inquiry.</p>	G1" BSP female-female	02	4,200/-	8,400/-
Subtotal					8,400/-

	GST 18%	1,512/-
	Grand Total	9,912/-

Amount in Words: Nine Thousand Nine Hundred and Twelve Rupees Only

4. TECHNICAL SPECIFICATIONS

Item 1 — Technical Compliance (per customer inquiry + datasheet)

Parameter	Specification
Valve type	Inline spring-loaded check valve (non-return)
Body material	AISI 316 / SS316 stainless steel
Connections	G1" BSP female inlet + G1" BSP female outlet
Max. working pressure	200 bar
Max. differential pressure	5 bar
Opening pressure	0.15 to 0.25 bar (within your acceptable range)
Nominal flow	160 l/min
Seals	Viton FKM (EPDM on request)
Mounting	In-line; any orientation
Reference	Equivalent to Kytola Model 2680-B G1"

5. COMMERCIAL TERMS & CONDITIONS

HSN Code	8481.80.30
Price Basis	Ex-Works Ahmedabad, India. Packing included.
GST	18% GST extra (IGST/CGST+SGST as applicable).
Delivery Time	7 to 10 working days from confirmed PO and advance — dispatch to Udaipur.
Packaging and Forwarding	2% Extra
Payment Terms	50% advance with PO; balance 50% before dispatch.
Offer Validity	30 days from quotation date

6. WARRANTY

12 months from date of dispatch against manufacturing and material defects. API 6D / NACE MR0175 compliant valves are warranted for sour service applications. Warranty covers material composition, heat treatment, hardness control, and NACE compliance per ISO 15156.

Yours faithfully,



Zahid Ranginwala
Director, Supreme Valves India



Gate Valve



Diaphragm Valve



Globe Valve



Check Valve



Needle Valve



Plug Valve



Butterfly Valve



Piston Valve



Relief Valve



Ball Valve