



SUPREME ENTERPRISE

Industrial Valves

4th Floor, Survey No. 235/A and 247/A, E/401, Nr. Bhattha School, Gyaspur, Ahmedabad, Gujarat 382405, India | Branch: Mehta House, Relief Road, Ahmedabad 380001
 GST 24AFAFS5839J1ZQ • IEC AFAFS5839J • info@supremevalves.in | www.supremevalves.in • +91 97732 78770

Doc. No.	SV-DATA-2026-API_600_GATE_VALVE_WCB_CLASS_900			API 600 Gate Valve Class 900# — WCB RF -- Technical Datasheet	Page	1 OF 1
Rev.	A				Date	13-Jun-2026
R	REFERENCES & RELATED DOCUMENTS					
R1	P&ID / Process Diagram	N/A -- Product Datasheet	Piping Material Spec.	N/A -- Product Datasheet		
R2	Project Standard / Spec.	API 600, ASME B16.34, ASME B16.10, API 598				
1	GENERAL					
2	P&ID No. / Tag No.	N/A -- Product Datasheet	Piping Class	ANSI Class 900		
3	Valve Tag / Item No.	N/A -- Product Datasheet	Quantity Required	As required		
4	Design Standard	API 600, ASME B16.34, ASME B16.10, API 598		Pressure Class / Rating	ANSI Class 900	
5	Valve Size, Inlet x Outlet	2" to 24" (DN50–DN600)		End Connection	RF Flanged, ASME B16.5 (BW / RTJ on request)	
6	Valve Type / Model	API 600 Gate Valve Class 900# — WCB RF		Operation Mode	OS&Y Rising Stem -- Handwheel / Gear Operator / Electric Actuator as required	
6A	Service / Application	Oil & Gas, Petrochemical, Water Treatment, Power Generation		Fluid State	Liquid / Gas / Steam (as applicable)	
7	DESIGN CONDITIONS					
8	Design Pressure	ANSI Class 900		Design Temp. Min / Max	-29°C to +425°C (standard) -- higher/lower on request	
9	Operating Pressure	ANSI Class 900		Operating Temp.	Ambient to +200°C (standard) -- project-specific on request	
10	Set / Relief Pressure	N/A -- Product Datasheet		Back Pressure	N/A -- Product Datasheet	
11	Fluid Handled / Service	Oil & Gas, Petrochemical, Water Treatment, Power Generation		Corrosion Allowance	As per project specification	
12	Required Capacity / Flow Rate	As per valve size and pressure class		Location / Installation	Indoor / Outdoor / Offshore / Marine (as applicable)	
13	VALVE OPERATION REQUIREMENT					
14	Type of Valve Operator	OS&Y Rising Stem -- Handwheel / Gear Operator / Electric Actuator as required		Actuator Specification	ISO 5211 pad (actuated) -- Electric / Pneumatic / Hydraulic on request	
15	Fail-Safe Position	As per project / application requirements		Accessories Required	Limit switches, positioners, solenoid valves, manual override -- on request	
16	VALVE MATERIAL SPECIFICATION (EQUIVALENT OR SUPERIOR)					
	Valve Part	Specified Material		Proposed Material (Supreme Valves India)		
	Body	As per project specification		ASTM A216 WCB (Carbon Steel)		
	Bonnet / Cover	As per standard		WCB or matching body grade		
	Trim (Disc / Seat)	As per standard		A216 WCB + 13Cr overlay, or CF8 / CF8M solid / Stellite 6 hardfaced or integral / soft (PTFE, Viton)		
	Stem / Spindle	As per standard		ASTM A182 F6a, F304, or F316		
	Gasket / Packing	As per standard		Spiral wound SS316 + graphite or RTJ ring		
	Bolting / Nuts	As per standard		A193 B7 / A194 2H (SS316 on request)		
17	TESTING, INSPECTION & CERTIFICATION REQUIREMENTS					
18	Hydrostatic Shell Test	Hydrostatic 23.0 MPa (3335 psi)		Seat / Pneumatic Test	Hydrostatic 16.8 MPa (2440 psi)	
19	NDT Requirements	100% MPI / DPT on machined surfaces (if specified) -- Radiography / Ultrasonic on request				
20	Required Certificates / MTC	EN 10204 3.1 MTC (standard) -- EN 10204 3.2 / third-party inspection on request				
21	Witness / Inspection Agency	Client / TPI representative (if specified)		Third Party Inspection	TUV / SGS / BV / Lloyds Register (client cost)	
22	PAINTING, PRESERVATION & PACKING					
23	Painting / Coating Specification	Standard: one coat primer + two coats synthetic enamel (colour per client spec) -- special coatings (epoxy, PTFE, rubber lining) on request				
24	Packing Requirement	Wooden cases / pallets with VCI protection -- sea-worthy packing for export on request				
26	NOTES					

1. This datasheet covers standard specifications for API 600 Gate Valve Class 900# — WCB RF.

2. Design Standard: API 600, ASME B16.34, ASME B16.10, API 598.
3. Application / Service: Oil & Gas, Petrochemical, Water Treatment, Power Generation.
4. Size Range: 2" to 24" (DN50–DN600). Pressure Rating: ANSI Class 900.
5. All valves are manufactured new and unused by an ISO 9001 compliant foundry.
6. Material Test Certificates (MTC) per EN 10204 3.1 provided as standard; EN 10204 3.2 available on request at additional cost.
7. Testing performed per ISO 5208 / API 598: shell test at 1.5x rated pressure, seat test at 1.1x rated pressure -- bubble-tight zero leakage.
8. Face-to-face dimensions per ASME B16.10 / BS 2080 / manufacturer standard unless otherwise specified.
9. Marking per MSS SP-25: Size, Pressure Class, Material, Heat Number, Tag Number, Serial Number, Flow Direction.
10. Alternative / upgraded materials: A217 WC6 / WC9 (high temp), A351 CF8M (stainless) available on request.
11. Actuated valves (electric, pneumatic, hydraulic) supplied with ISO 5211 mounting pad and position indicator.
12. Third-party inspection by TUV, SGS, Bureau Veritas, or Lloyds Register available on request at client cost.
13. This datasheet is for general reference. Firm specifications to be confirmed upon receipt of confirmed Purchase Order with technical requirements.
14. For specific project requirements, deviation forms, or material substitutions, please contact our engineering team.

RH REVISION HISTORY			
Rev.	Date	Description of Change	Prepared / Reviewed / Approved
A	13-Jun-2026	Initial issue -- Product datasheet generated from standard catalogue	Supreme Valves India -- Technical Department
AP DOCUMENT APPROVAL			
<p style="text-align: center;">PREPARED BY Supreme Valves India -- Technical Department, Ahmedabad</p> <p>_____</p> <p style="text-align: center;">Signature / Date</p>		<p style="text-align: center;">REVIEWED BY</p> <p>_____</p> <p style="text-align: center;">Name / Signature / Date</p>	
		<p style="text-align: center;">APPROVED BY</p> <p>_____</p> <p style="text-align: center;">Name / Signature / Date</p>	