



# SUPREME ENTERPRISE

Industrial Valves

4th Floor, Survey No. 235/A and 247/A, E/401, Nr. Bhattha School, Gyaspur, Ahmedabad, Gujarat 382405, India | Branch: Mehta House, Relief Road, Ahmedabad 380001  
GST 24AFAFSS5839J1ZQ • IEC AFAFSS5839J • info@supremevalves.in | www.supremevalves.in • +91 97732 78770

Doc. No.	SV-DATA-2026-FLOAT_CHECK_VALVE_FLANGED_CLASS_150			Page	1 OF 1
Rev.	A				Date
<b>Float Check Valve Flanged Class 150 -- Technical Datasheet</b>					
<b>R</b>	<b>REFERENCES &amp; RELATED DOCUMENTS</b>				
R1	P&ID / Process Diagram	N/A -- Product Datasheet	Piping Material Spec.	N/A -- Product Datasheet	
R2	Project Standard / Spec.	ASME B16.1, ASME B16.34, API 598			
1	<b>GENERAL</b>				
2	P&ID No. / Tag No.	N/A -- Product Datasheet	Piping Class	Class 150	
3	Valve Tag / Item No.	N/A -- Product Datasheet	Quantity Required	As required	
4	Design Standard	ASME B16.1, ASME B16.34, API 598	Pressure Class / Rating	Class 150	
5	Valve Size, Inlet x Outlet	2" to 12" (DN50–DN300)	End Connection	Flanged, ASME B16.1 / ASME B16.5	
6	Valve Type / Model	Float Check Valve Flanged Class 150	Operation Mode	Top-hinged float disc provides automatic closure with minimal head loss for tank outlets and pump suction lines	
6A	Service / Application	Oil & Gas, Petrochemical, Water Treatment, Power Generation	Fluid State	Liquid / Gas / Steam (as applicable)	
7	<b>DESIGN CONDITIONS</b>				
8	Design Pressure	Class 150	Design Temp. Min / Max	-29°C to +425°C (standard) -- higher/lower on request	
9	Operating Pressure	Class 150	Operating Temp.	Ambient to +200°C (standard) -- project-specific on request	
10	Set / Relief Pressure	N/A -- Product Datasheet	Back Pressure	N/A -- Product Datasheet	
11	Fluid Handled / Service	Oil & Gas, Petrochemical, Water Treatment, Power Generation	Corrosion Allowance	As per project specification	
12	Required Capacity / Flow Rate	As per valve size and pressure class	Location / Installation	Indoor / Outdoor / Offshore / Marine (as applicable)	
13	<b>VALVE OPERATION REQUIREMENT</b>				
14	Type of Valve Operator	Top-hinged float disc provides automatic closure with minimal head loss for tank outlets and pump suction lines	Actuator Specification	ISO 5211 pad (actuated) -- Electric / Pneumatic / Hydraulic on request	
15	Fail-Safe Position	As per project / application requirements	Accessories Required	Limit switches, positioners, solenoid valves, manual override -- on request	
16	<b>VALVE MATERIAL SPECIFICATION (EQUIVALENT OR SUPERIOR)</b>				
	Valve Part	Specified Material	Proposed Material (Supreme Valves India)		
	Body	As per project specification	Cast Iron ASTM A126 Class B / Ductile Iron A536		
	Bonnet / Cover	As per standard	As per standard / matching body grade		
	Trim (Disc / Seat)	As per standard	Bronze / SS304 hollow float / Bronze or resilient EPDM/NBR		
	Stem / Spindle	As per standard	SS304 / SS316		
	Gasket / Packing	As per standard	Non-asbestos / EPDM		
	Bolting / Nuts	As per standard	A193 B7 / A194 2H (SS304 on request)		
17	<b>TESTING, INSPECTION &amp; CERTIFICATION REQUIREMENTS</b>				
18	Hydrostatic Shell Test	Hydrostatic 3.1 MPa (450 psi)	Seat / Pneumatic Test	Hydrostatic 2.2 MPa (320 psi)	
19	NDT Requirements	100% MPI / DPT on machined surfaces (if specified) -- Radiography / Ultrasonic on request			
20	Required Certificates / MTC	EN 10204 3.1 MTC (standard) -- EN 10204 3.2 / third-party inspection on request			
21	Witness / Inspection Agency	Client / TPI representative (if specified)	Third Party Inspection	TUV / SGS / BV / Lloyds Register (client cost)	
22	<b>PAINTING, PRESERVATION &amp; PACKING</b>				
23	Painting / Coating Specification	Standard: one coat primer + two coats synthetic enamel (colour per client spec) -- special coatings (epoxy, PTFE, rubber lining) on request			
24	Packing Requirement	Wooden cases / pallets with VCI protection -- sea-worthy packing for export on request			
26	<b>NOTES</b>				

1. This datasheet covers standard specifications for Float Check Valve Flanged Class 150.

2. Design Standard: ASME B16.1, ASME B16.34, API 598.
3. Application / Service: Oil & Gas, Petrochemical, Water Treatment, Power Generation.
4. Size Range: 2" to 12" (DN50–DN300). Pressure Rating: Class 150.
5. All valves are manufactured new and unused by an ISO 9001 compliant foundry.
6. Material Test Certificates (MTC) per EN 10204 3.1 provided as standard; EN 10204 3.2 available on request at additional cost.
7. Testing performed per ISO 5208 / API 598: shell test at 1.5x rated pressure, seat test at 1.1x rated pressure -- bubble-tight zero leakage.
8. Face-to-face dimensions per ASME B16.10 / BS 2080 / manufacturer standard unless otherwise specified.
9. Marking per MSS SP-25: Size, Pressure Class, Material, Heat Number, Tag Number, Serial Number, Flow Direction.
10. Alternative / upgraded materials: Bronze and SS316 body variants available on request.
11. Actuated valves (electric, pneumatic, hydraulic) supplied with ISO 5211 mounting pad and position indicator.
12. Third-party inspection by TUV, SGS, Bureau Veritas, or Lloyds Register available on request at client cost.
13. This datasheet is for general reference. Firm specifications to be confirmed upon receipt of confirmed Purchase Order with technical requirements.
14. For specific project requirements, deviation forms, or material substitutions, please contact our engineering team.

RH REVISION HISTORY			
Rev.	Date	Description of Change	Prepared / Reviewed / Approved
A	13-Jun-2026	Initial issue -- Product datasheet generated from standard catalogue	Supreme Valves India -- Technical Department
AP DOCUMENT APPROVAL			
	<b>PREPARED BY</b> Supreme Valves India -- Technical Department, Ahmedabad  _____ Signature / Date	<b>REVIEWED BY</b>  _____ Name / Signature / Date	<b>APPROVED BY</b>  _____ Name / Signature / Date

SUPREME ENTERPRISE -- Industrial Valves • Trusted Exporter of Industrial Valves • This is a computer-generated technical datasheet. Firm specifications confirmed against Purchase Order.