



SUPREME ENTERPRISE

Industrial Valves

4th Floor, Survey No. 235/A and 247/A, E/401, Nr. Bhattha School, Gyaspur, Ahmedabad, Gujarat 382405, India | Branch: Mehta House, Relief Road, Ahmedabad 380001
 GST 24AFAFS5839J1ZQ • IEC AFAFS5839J • info@supremevalves.in | www.supremevalves.in • +91 97732 78770

Doc. No.	SV-DATA-2026-NAB BALL VALVE API 6D FOR SEAWATER			Page	1 OF 1
Rev.	A			Date	13-Jun-2026
NAB Ball Valve – API 6D for Seawater -- Technical Datasheet					
R	REFERENCES & RELATED DOCUMENTS				
R1	P&ID / Process Diagram	N/A -- Product Datasheet	Piping Material Spec.	N/A -- Product Datasheet	
R2	Project Standard / Spec.	API 6D, ASME B16.34, API 607, API 598			
1	GENERAL				
2	P&ID No. / Tag No.	N/A -- Product Datasheet	Piping Class	Class 150 / 300 (PN16 / PN25)	
3	Valve Tag / Item No.	N/A -- Product Datasheet	Quantity Required	As required	
4	Design Standard	API 6D, ASME B16.34, API 607, API 598		Pressure Class / Rating	Class 150 / 300 (PN16 / PN25)
5	Valve Size, Inlet x Outlet	1/2" to 24" (DN15 – DN600)		End Connection	Flanged RF per ASME B16.5 / Butt Weld
6	Valve Type / Model	NAB Ball Valve – API 6D for Seawater		Operation Mode	Floating or trunnion ball in cast Nickel Aluminium Bronze -- outstanding seawater erosion-corrosion and biofouling resistance for desalination and offshore firewater service; API 607 fire-safe
6A	Service / Application	Seawater Systems, Desalination Plants, Offshore Platforms, Marine & Shipbuilding		Fluid State	Liquid / Gas / Steam (as applicable)
7	DESIGN CONDITIONS				
8	Design Pressure	Class 150 / 300 (PN16 / PN25)		Design Temp. Min / Max	-29°C to +425°C (standard) -- higher/lower on request
9	Operating Pressure	Class 150 / 300 (PN16 / PN25)		Operating Temp.	Ambient to +200°C (standard) -- project-specific on request
10	Set / Relief Pressure	N/A -- Product Datasheet		Back Pressure	N/A -- Product Datasheet
11	Fluid Handled / Service	Seawater Systems, Desalination Plants, Offshore Platforms, Marine & Shipbuilding		Corrosion Allowance	As per project specification
12	Required Capacity / Flow Rate	As per valve size and pressure class		Location / Installation	Indoor / Outdoor / Offshore / Marine (as applicable)
13	VALVE OPERATION REQUIREMENT				
14	Type of Valve Operator	Floating or trunnion ball in cast Nickel Aluminium Bronze -- outstanding seawater erosion-corrosion and biofouling resistance for desalination and offshore firewater service; API 607 fire-safe		Actuator Specification	ISO 5211 pad (actuated) -- Electric / Pneumatic / Hydraulic on request
15	Fail-Safe Position	As per project / application requirements		Accessories Required	Limit switches, positioners, solenoid valves, manual override -- on request
16	VALVE MATERIAL SPECIFICATION (EQUIVALENT OR SUPERIOR)				
	Valve Part	Specified Material	Proposed Material (Supreme Valves India)		
	Body	As per project specification	Nickel Aluminium Bronze (NAB) -- C95800 / CuAl10Fe5Ni5 (ASTM B148 / BS EN 1982)		
	Bonnet / Cover	As per standard	As per standard / matching body grade		
	Trim (Disc / Seat)	As per standard	NAB C95800 / SS316 hard chrome plated / RPTFE / Devlon V (seawater rated)		
	Stem / Spindle	As per standard	NAB / SS316, blowout-proof, anti-static		
	Gasket / Packing	As per standard	PTFE / Graphite		
	Bolting / Nuts	As per standard	Super Duplex / Monel K500		
17	TESTING, INSPECTION & CERTIFICATION REQUIREMENTS				
18	Hydrostatic Shell Test	Hydrostatic 3.1 MPa (450 psi)		Seat / Pneumatic Test	Hydrostatic 2.2 MPa (320 psi)
19	NDT Requirements	100% MPI / DPT on machined surfaces (if specified) -- Radiography / Ultrasonic on request			
20	Required Certificates / MTC	EN 10204 3.1 MTC (standard) -- EN 10204 3.2 / third-party inspection on request			
21	Witness / Inspection Agency	Client / TPI representative (if specified)		Third Party Inspection	TUV / SGS / BV / Lloyds Register (client cost)
22	PAINTING, PRESERVATION & PACKING				
23	Painting / Coating Specification	Standard: one coat primer + two coats synthetic enamel (colour per client spec) -- special coatings (epoxy, PTFE, rubber lining) on request			
24	Packing Requirement	Wooden cases / pallets with VCI protection -- sea-worthy packing for export on request			

26 NOTES

1. This datasheet covers standard specifications for NAB Ball Valve – API 6D for Seawater.
2. Design Standard: API 6D, ASME B16.34, API 607, API 598.
3. Application / Service: Seawater Systems, Desalination Plants, Offshore Platforms, Marine & Shipbuilding.
4. Size Range: 1/2" to 24" (DN15 – DN600). Pressure Rating: Class 150 / 300 (PN16 / PN25).
5. All valves are manufactured new and unused by an ISO 9001 compliant foundry.
6. Material Test Certificates (MTC) per EN 10204 3.1 provided as standard; EN 10204 3.2 available on request at additional cost.
7. Testing performed per ISO 5208 / API 598: shell test at 1.5x rated pressure, seat test at 1.1x rated pressure -- bubble-tight zero leakage.
8. Face-to-face dimensions per ASME B16.10 / BS 2080 / manufacturer standard unless otherwise specified.
9. Marking per MSS SP-25: Size, Pressure Class, Material, Heat Number, Tag Number, Serial Number, Flow Direction.
10. Alternative / upgraded materials: Aluminium Bronze C95500 and Duplex SS trims available on request -- ideal for seawater & desalination.
11. Actuated valves (electric, pneumatic, hydraulic) supplied with ISO 5211 mounting pad and position indicator.
12. Third-party inspection by TUV, SGS, Bureau Veritas, or Lloyds Register available on request at client cost.
13. This datasheet is for general reference. Firm specifications to be confirmed upon receipt of confirmed Purchase Order with technical requirements.
14. For specific project requirements, deviation forms, or material substitutions, please contact our engineering team.

RH REVISION HISTORY			
Rev.	Date	Description of Change	Prepared / Reviewed / Approved
A	13-Jun-2026	Initial issue -- Product datasheet generated from standard catalogue	Supreme Valves India -- Technical Department
AP DOCUMENT APPROVAL			
<p style="text-align: center;">PREPARED BY Supreme Valves India -- Technical Department, Ahmedabad</p> <p>_____</p> <p style="text-align: center;">Signature / Date</p>		<p style="text-align: center;">REVIEWED BY</p> <p>_____</p> <p style="text-align: center;">Name / Signature / Date</p>	<p style="text-align: center;">APPROVED BY</p> <p>_____</p> <p style="text-align: center;">Name / Signature / Date</p>